


Product data sheet

FREESTANDING LUMINAIRE TWEAK ESSENTIAL OFFICE SINGLE HEAD F
2004.7061 - TWEAK2 ESS S1U2050 LED9400-840 SR 0IFSEDI EU
REGENT



Freestanding luminaire Tweak Essential Office single head face side, with LED, system power: 68 W, standby power 0.5 W, luminous flux of luminaire 9400 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 ($UGR < 19$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, 19%/81%, common dimmable and switchable, without control element, luminaire head 2x90°adjustable, one-piece housing in die-cast aluminium, silver, VAG E 1, thermo painted, office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, with interface module/switch on the base plate, 1 integral control gear, SensoDim®, with light/movement sensor, base plate, U-shaped, 2m power supply cable with IEC 7/7 european plug, ingress protection IP20, protection class I, glow wire test 650 °C, this product contains a light source of energy efficiency class C, and EPREL registration number: 1140598, L = 734 mm, B = 215 mm, total height = 2050 mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	68 W	CRI	80
Total flux	9400 lm	LOR	100%
Luminous efficacy	138 lm/W	ULOR	78%
		Total power	68 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 31.77 in
Width: 17.80 in
Height: 80.79 in
Weight: 20.46 kg

Adjustability

Free

Design

Color of housing: Silver gray

Electric

System power: 68 W
Appliance Class: I

Protection

IP: 20