


Product data sheet

CIRCULAR DOWNWARD Ø600 RECESSED
CS5A-00W9AZDUEF
LEDSC4



LedsC4 Circular Downward ø600 Recessed CS5A-00W9AZDUEFV1 Pendant for indoor use. For downlighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 3.4 Product width or diameter (mm): 622 Product height (mm): 3000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEAN WELL. Maximum power of light source: 30W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 16.4. Photobiological risk: RG1. Real flux (lm): 2318. Real lm/W: 70. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 33. Power factor: 0.90. Dimmable equipment included: DALI-2.

Light output 1



1 x LED			
Nominal lamp power	33 W	LOR	100%
Lamp flux	2318 lm	Total flux	2318 lm
Luminous efficacy	70 lm/W	Total power	33 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 1.77 in

Adjustability

Fixed

Electric

System power: 33 W
Appliance Class: I

Protection

IP: 20