


# Product data sheet

OUTDOOR WALL 1-8H/D CGLINE+ H (SET TO 3 H OPERATION)  
40071354879  
EATON EMERGENCY LIGHTING



• LED self-contained luminaire with high protection class (IP65) for indoor and outdoor use • With automatic test for reduced inspection effort • Universal use for maintained and non-maintained operation and for 1 h, 3 h or 8 h operation • For autonomous installation or connection to the CGLine+ monitoring system • Robust construction from aluminium diecast and high impact resistant cover made of polycarbonate • Suitable for use in food processing industry acc. IFS (Atlantic LED R and Atlantic LED O) • Suitable for operational areas with fire hazard (D mark) • Environmentally-friendly due to modern lithium ion technology • Optional with self-regulating battery heater for use at low temperature up to -20°C • Low operating costs via low connected load • Minimum maintenance effort via use of LEDs with high service life (50,000 hours)) • Available with special optics for escape route illumination or wide area illumination • High spacing by double optics technology and highly efficient HighPower LEDs • Simple fault analysis and status display via bicolor LED and testing button • 1 minute switch-back delay after mains return • Blocking function prevents unintended discharge during idle operating times (only with CGLine+ WEB-Controller)

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5 W	CRI	70
Total flux	111 lm	LOR	100%
Luminous efficacy	22 lm/W	Total power	5 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 11.93 in  
Width: 7.24 in  
Height: 6.30 in

## Adjustability

Fixed

## Electric

System power: 5 W  
Suitable for feed-through wiring  
Appliance Class: I

## Information regarding emergency functions

Emergency lighting only  
Emergency power supply: Single battery 1 h, Single battery 3 h, Single battery 8 h  
Emergency sign: N/A

## Protection

IP: 65  
IK: 10