

# Product data sheet

FLAT POLYMERO


311556.002.6.76

RZB



Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 620, H 160 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3200lm System power: 28W Beam Angle: 117° Number of fittings B10A: 22 Number of fittings B16A: 40 Inrush current: 34A Unified Glare Ratio: 18,9 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	3200 lm	LOR	100%
Luminous efficacy	114 lm/W	ULOR	8%
		Total power	28 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 6.30 in

Diameter: 24.41 in

## Adjustability

Fixed

## Electric

System power: 28 W

## Protection

IP: 40

IK: 10