Product data sheet

CUDDLE MINI LED D4I 36 4000K T4
2227232/4/T4/10KV
ROSA



IP 66

One of the most frequently chosen luminaires. The basic version of the product from the CUDDLE MINI LED series. In a compact size, made of aluminium - in the standard version the body is anodised in inox and black. Installed on an extension arm with a ⌀ 60 x 100 mm ending. Most often, it illuminates city and residential streets, pedestrian routes and car parks. It has a protection class of IP 66 for the optical part and the power input system. The luminaire is equipped with PMMA lenses, an interchangeable LED module and a tempered glass diffuser. The expected service life of the product is L90B10 - 100,000. h. The input voltage frequency is 50/60Hz. Power factor ≥0.95. The fixture has 16 LEDs. It is possible to connect the luminaire to an external control system and/or sensors via a socket compatible with Zhaga Book 18.

Light output 1



1 x LED

Nominal lamp power	39 W	LOR	84%
Lamp flux	6650 lm	Total flux	5554 lm
Luminous efficacy	171 lm/W	Total power	39 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 20.87 in
Width: 8.11 in
Height: 3.07 in

Adjustability

Fixed

Electric

System power: 39 W

Protection

IP: 66