
Product data sheet


LTUB60 SUT 1120 1500 VWW D/I OPAL WH
L61ST112LOIO927NW
LAMP



IP 20 IK 07

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Light output 1



1 x LED

Nominal lamp power	17.8 W	LOR	100%
Lamp flux	1430 lm	Total flux	1429 lm
Luminous efficacy	80 lm/W	Total power	17.8 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 34.02 in
Width: 2.76 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 17.8 W
Appliance Class: I

Protection

IP: 20
IK: 07