

Product data sheet


VISIO - 250W - 2000MM - AREA BROAD - EMERGENCY
EVO250LAB
THORLUX LIGHTING



IP
20

The Visio exemplifies the supreme performance that is expected of Thorlux luminaires providing up to 49,760 lumens and an efficiency of up to 170.1 luminaire lumens per circuit watt. The Visio is available in five wattages and four light distributions ensuring there is a solution for a wide range of mounting heights, spacings and applications. Extremely long life, fast installation and easy maintenance of integral emergency versions are key features of Visio. SmartScan versions have a unique sensor that can be optimised for use up to 18m, maintaining excellent occupancy detection. SmartScan "wireless" versions eliminate the requirement for control cabling often associated with retro-fit installations. Applications: General open factory areas, storage, high level racking aisles, retail and commercial areas.

Light output 1 (integrated, emergency)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 264 W | CRI | 80 |
| Total flux | 43100 lm | LOR | 100% |
| Luminous efficacy | 163 lm/W | Total power | 264 W |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 79.06 in
Width: 8.94 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 264 W

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 20