


Product data sheet

3F LINUX L 60 LED BAT L1778 (IP40)
A20083
3F FILIPPI



Light unit for structure continues 3F Linux S. ILLUMINOTECHNICAL Luminous efficiency 100% (DLOR 97%, ULOR 3%). Initial luminous flux of the luminaire 9876 lm. Double asymmetric direct distribution. Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 22.2 - 23.4. Beam angle: 23° - 70°. Luminous efficacy 178 lm/W. Lifetime (L93/B10): 30000 h. (tq+25°C) Lifetime (L90/B10): 50000 h. (tq+25°C) Lifetime (L85/B10): 80000 h. (tq+25°C) Lifetime (L80/B10): 100000 h. (tq+25°C) Lifetime (L85/B10): 50000 h. (tq+40°C) Sudden decreased luminous flux after 50000 hours: 0% (C0). Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471). In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards. SOURCE Linear LED module 60W/840. Energy efficiency class (UE 2019/2020 - UE 2019/2015): C. CIE 13.3 Colour rendering index: CRI >80 (R9 <50%). IES TM-30 Fidelity Index: Rf = 84 Rg = 95. CCT nominal colour temperature 4000 K. Colour initial tolerance (MacAdam): SDCM 3. MECHANICAL Light unit in hot-galvanised steel, painted in white polyester base with fixing springs and retractable safety hooks in stainless steel. Lenses BAT with double asymmetrical distribution, in methacrylate (PMMA) with external flat surface. Luminaire with limited surface temperature. - D - (EN 60598-2-24) Dimensions: 1778x62 mm, height 65 mm. Weight 2.32 kg. IP40 protection degree. Mechanical strength to impacts IK06 (1 joule). Glow-wire test resistance 650°C. ELECTRICAL Halogen Free electronic wiring 230V-50/60Hz, power factor 0.95, THD <25%, constant output current, class I, 1 driver. Power of the luminaire 55.5 W. ENEC - CE. SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC. Ambient temperature from 0°C to +40°C. Temperature class T6 max 85°C. Connection to the structure with 3-pin plug with phase selection (H05Z-U Halogen Free cable section 0.5 mm² HT90). Relative humidity UR: <85%. INSTALLATION Ceiling / Suspended / Wall. All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com. STRUCTURE Hot-galvanised wired structure, painted in polyester base white, obtained through rolling process. Saline-mist resistance equal to 300hrs and damp resistance equal to 700hrs. Through-wiring 5 or 7 poles with cables H07Z-U Halogen Free section 2.5 mm² HT90, with quick connecting terminal, irreversible, start / end and intermediate power towers. Linear connecting element in hot galvanised steel already mounted on one end to form continuous channels, only L3556 structures. A20017 - 3F Linux S 5P L3556, structure with through-wiring 5-pole. A20019 - 3F Linux S 5P L1778, structure with through-wiring 5-pole. A20024 - 3F Linux S 7P L3556, structure with through-wiring 7-pole. A20026 - 3F Linux S 7P L1778, structure with through-wiring 7-pole. APPLICATIONS Suitable product for food production plants (HACCP), IFS (Food Version 6), BRC (GSFS Food Version 7). In commercial environments, exhibition areas, shops and stores. WARNING Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	55.5 W	CRI	80
Total flux	9876 lm	LOR	100%
Luminous efficacy	178 lm/W	ULOR	3%
		Total power	55.5 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 70.00 in

Width: 2.44 in

Height: 1.26 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 55.5 W

Appliance Class: I

Protection

IP: 40

IK: 06