


Product data sheet

MINGATA MINI
612178.004.76
RZB



Series: MINGATA mini Functional pole-side and pole-top luminaire in a modern design. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Pole-top fixing with integrated cable routing and stainless steel screws. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass. Asymmetrical light distribution for area lighting (P or C lighting classes). Luminaires for pole top Ø 76 mm (with optional adapter sleeve, also suitable for pole top Ø 60 mm). Tool-free maintenance / replacement by Eccentric-Lock system with disconnect plug and Hybrid-Lock-System. 4 x 1.0 mm² connecting cable included, length 8 m. Colour: silver, matt (approx. RAL 9006) Length: 530 mm Width: 270 mm Height: 100 mm Lamp: LED System power: 45 W Rated luminous flux: 6000 lm Luminous efficiency: 133 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 66

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	45 W	CRI	70
Total flux	6000 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	50%
		Total power	45 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 10.63 in
Width: 20.87 in
Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 45 W

Protection

IP: 66
IK: 08