


Product data sheet

SCOUT 204.940.35.2 35°
SCOUT 204.940.35.2
LTS LICHT & LEUCHTEN



flexible track-mounted spotlight in separated design with cylindrical light-head, light-head rotates through 355° and pivots through 90° via integrated articulated arm, outstanding ease of maintenance, no UV and thermal emissions, light-head made from die-cast aluminium, innovative thermal management with design-integrated passive cooling, high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting, ballast housing made from aluminium, clear and reflection-free EnergyVision safety glass, 3-phase track adapter, ballast (LED converter) integrated Lamp: LED Spot | 940 | CRI 90 | 4000 K Lifetime: L90 B50 50.000 h / L80 B50 100.000 h / L80 B20 50.000 h EPREL light sources: 848115 beam angle: 35° beam range: 35° Protection class: I Type of protection: IP20 Standards: CE,RoHS Diameter of light head: 96 mm Dimensions (LxBxH): 212 x 96 x 164 mm Weight: 1.155 kg Colour: silver (article no. 660571), black (article no. 660572), white (article no. 660573) Accessories: ST-A 10/9000A-1-ST surface-mounted track ONETrack Advance with data bus (length: 1000 mm) ST-A 20/9000A-2-ST surface-mounted track ONETrack Advance with data bus (length: 2000 mm) ST-A 30/9000A-3-ST surface-mounted track ONETrack Advance with data bus (length: 3000 mm) ST-A 40/9000A-4-ST surface-mounted track ONETrack Advance with data bus (length: 4000 mm) ST-A MONO/9000-BPU-D 3-phase surface-mounted monopoint with bus option ST-E 10/9000-1-R recessed track ONETrack with data bus (length: 1000 mm) ST-E 20/9000-2-R recessed track ONETrack with data bus (length: 2000 mm) ST-E 30/9000-3-R recessed track ONETrack with data bus (length: 3000 mm) ST-E 40/9000-4-R recessed track ONETrack with data bus (length: 4000 mm) ST-E MONO/9000-BPU-D 3-phase recessed monopoint with bus option ZBK 13 anti-glare flaps ZBW 87 honeycomb louvre Manufacture: LTS Type: SCOUT 204.940.35.2

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 37.5 W | CRI | 90 |
| Total flux | 4390 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 37.5 W |

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.46 in
Diameter: 3.78 in

Electric

System power: 37.5 W
Appliance Class: I

Protection

IP: 20