Product data sheet


HALO SUSP. CENTRAL MERGING DI/ID SILVER 760MM
R48Z076-9006E2930L3S
PLANLICHT



IP 40


LED HO 3000K CRI>90 80,5W 8516lm DALI https://katalog.planlicht.com/en-gb/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5.7 W	CRI	90
Total flux	484 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	5.7 W

Mounting mode

Pendant

Shape and measurements

Length: 29.92 in
Width: 29.92 in
Height: 2.44 in

Adjustability

Fixed

Electric

System power: 45.6 W

Protection

IP: 40
Designation labels: CE