Product data sheet

LESS IS MORE 50
312614.002
RZB



IP 20 IK 03

Series: LESS IS MORE 50 Linear wall luminaires. Housing made of extruded aluminium profile, powder-coated. End cap made of aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Direct 50%, indirect 50% light emission. Suitable for Wall (surface). LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. With sensors or as a safety luminaire on request. Colour: traffic white, matt (RAL 9016) Length: 1967 mm Width: 67 mm Height: 75 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 3000K Colour rendering index (CRI) 2: 80 System power: 34 W Rated luminous flux: 4550 lm Beam angle Down: 107° / 108° Luminous efficiency: 134 lm/W Control gear: Regulated power supply Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34 W	CRI	80
Total flux	4550 lm	LOR	67%
Luminous efficacy	134 lm/W	ULOR	14%
		Total power	34 W

Mounting mode

Wall mounted

Shape and measurements

Length: 2.64 in
Width: 77.44 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 34 W

Protection

IP: 20
IK: 03