

Product data sheet

DISC 480 TW WHITE 3290LM (@2700K) 2700-6500K RA>80 TUNABLE WHITE DALI TYPE 8


7021986060096

SG ARMATUREN



Energy efficient surface-mounted LED luminaire with a slim profile ensuring a modern look. Square and round available in multiple sizes and lumens. Prismatic diffuser provides a glare-free light. The luminaire is produced in a matt black or white powder-coated aluminium finish. Simple installation with quick connections between fixture and back plate that can be screwed straight onto all known ceiling boxes. Visible cabling also possible. Tunable White LEDDim or DALI Type 8. Light distribution Direct Light technic LED (not exchangeable) 36W 2700-6500K Ra>80 SDCM 3 L80/B20 >100,000 hrs L90 >50,000 hrs Control/Dimming Tunable White DALI Type 8 Protection Class II IP20 IK10 Materials and finish Housing: Aluminium Colour: White Optics: PMMA (Acrylate) Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 10, B16: 16, C10: 16, C16: 26

Light output 1



1 x LED

Nominal lamp power	36 W	LOR	100%
Lamp flux	3290 lm	Total flux	3290 lm
Luminous efficacy	91 lm/W	Total power	36 W
CCT	2700 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 18.50 in

Width: 18.50 in

Height: 2.15 in

Adjustability

Fixed

Electric

System power: 36 W

Color adjustable

Appliance Class: II

Protection

IP: 20

IK: 10