


Product data sheet

PTECD L20 LE3 & PTEC D SSR * **
PROTEC LED EMERGENCY
DEXTRA




Protec LED - Ø174mm, IP20 Recessed downlighter with ABS housing and bezel, zinc plated spring steel fixing clips, anodised aluminium reflectors. LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest Emergency Lumen Values: No Coloured Ring: Opti-Spec: 367, Opti-Sat: 357 Drop Glass Ring: Opti-Spec: 344, Opti-Sat: 335 IP44 Cover: Opti-Spec: 343, Opti-Sat: 333 Microprism Diffuser: Opti-Spec: 274, Opti-Sat: 263 Opal Diffuser: Opti-Spec: 262, Opti-Sat: 243 S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* Replace * with WH for white ring or GY for Grey Replace ** with WHI - White halo GRE - Green halo ORA - Mango halo BLE - Blue halo

Light output 1 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	388 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	4 W

Light output 2 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	16.5 W	CRI	80
Total flux	1859 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	16.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.80 in
Diameter: 6.89 in

Adjustability

Fixed

Electric

System power: 20.5 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20

Designation labels: CE