Product data sheet

DOWNTOWN TRIM Ø215 03.0407/TC-TEL/42W


FLOS






Luminaires for embedded installation indoor with fluorescent lamps and of halogenuro metalist. Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	Socket	Gx24Q-4
Lamp flux	3200 lm	LOR	49%
Luminous efficacy	49 lm/W	Total flux	1577 lm
CCT	4000 K	Total power	32 W
CRI	79		
Luminous efficacy CCT	49 lm/W 4000 K	Total flux	1577 lm



1 x Compact fluorescent lamp	
------------------------------	--

Nomina	al lamp power	42 W	Socket	Gx24Q-4
Lamp fl	lux	3200 lm	LOR	49%
Lumino	ous efficacy	49 lm/W	Total flux	1577 lm
CCT		3000 K	Total power	32 W
CRI		84		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.36 in Diameter: 8.46 in

Adjustability

Fixed

Electric

Protection

IP: 23

System power: 32 W