


Product data sheet

3583 LED 1-8H/D CGLINE+ (SET TO 8 H OPERATION)
40071353365
EATON EMERGENCY LIGHTING



• Self-contained safety luminaire with LED technology for recessed mounting with round bezel with automatic test for reduced inspection effort • Universal use for maintained and non-maintained operation and for 1 h, 3 h or 8 h operation • For autonomous installation or connection to the CGLine+ monitoring system • Environmentally-friendly due to modern lithium ion technology • Low operating costs via low connected load • Minimum maintenance effort via high LED service life (50,000 hours) • Simple fault analysis and status display via bicolor LED and testing button • 1 minute switch-back delay after mains return • Blocking function prevents unintended discharge during idle operating times (only with CGLine+ WEB-Controller) • Common ceiling cut-out diameter of 68 mm

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	6.6 W	CRI	70
Total flux	128 lm	LOR	100%
Luminous efficacy	19 lm/W	Total power	6.6 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.15 in
Width: 3.15 in
Height: 1.38 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 6.6 W
Suitable for feed-through wiring
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Single battery 1 h, Single battery 3 h, Single battery 8 h
Emergency sign: N/A

Protection

IP: 20
IK: 03