
Product data sheet


PURE3 SQUARE SURFACE WHITE PRISM.
P33A14Q-9016C1930L1M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 20


LED LO 3000K 69,1W 7424lm CRI90 ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 28,4% https://katalog.planlicht.com/en-gb/search?q=pure%203

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17.28 W	CRI	90
Total flux	1856 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	34%
		Total power	17.28 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17.28 W	CRI	90
Total flux	1856 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	34%
		Total power	17.28 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.28 W	CRI	90
Total flux	1856 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	34%
		Total power	17.28 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.28 W	CRI	90
Total flux	1856 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	34%
		Total power	17.28 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 58.19 in
Width: 58.19 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 69.1 W

Protection

IP: 20