

Product data sheet


LXEW4-35MH-CAW-EU
CURRENT



IP
67

The LXEW vaportite is a high/low bay fixture for demanding areas. Standard with IP65, IP66, IP67, Wet Label, F1 Weather and UL Sanitation to NSF Standards. High efficacy LED in choice of lumen packages and colors, Long-life, 60,000 hour LEDs at L80 for reduced life cycle maintenance costs, Available in narrow or wide distribution, IP65, IP66, and IP67 rated, 1500 PSI High Pressure Hose down rating, Fiberglass housing with F1 weatherability rating, standard, Gasket is non-porous to ensure seal, Impact modified acrylic lenses, Lens selections includes clear, frosted, or clear polycarbonate, Lens firmly secured with tamper resistance ready latches, Lens is tethered and gear tray hinges for ease of maintenance, Stainless steel latching and mounting straps optional, Removable gear tray electrical access, V-Hook mounting brackets included standard, UL Sanitation certified to NSF standards, Standard ambient -40°C to 50°C, IK10 rated when ordered with polycarbonate lens, DLC® (DesignLights Consortium) Qualified, with some Premium Qualified configurations - see www.designlights.org, Five year warranty,

Light output 1 (integrated)



Lamp type	LED	CCT	3500 K
Nominal lamp power	137.5 W	CRI	80
Total flux	17921 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	137.5 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 14.06 in
Width: 50.98 in
Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 137.5 W

Protection

IP: 67