


# Product data sheet

MIC 3 FLOODLIGHTS,PROJECTORS  
MI-50381-M-W40-A50231  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 200,000, 300,000 - Life time L80B10 Ta 50° 490,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4032 K |
| Nominal lamp power | 28.7 W   | CRI         | 80     |
| Total flux         | 2901 lm  | LOR         | 100%   |
| Luminous efficacy  | 101 lm/W | Total power | 28.7 W |

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Height: 12.87 in  
Diameter: 7.76 in  
Weight: 3.7 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 28.7 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 07  
Surface temperature: 40°C