

# Product data sheet


GAN GALLEON AREA/ROADWAY LUMINAIRE  
GAN-SA5A-722-U-SL4  
COOPER LIGHTING



IP  
47

Choice of 16 high-efficiency, patented AccuLED Optics™, Lumen packages range from 4,200 – 80,800 (34W – 640W), Available in 2200K, 2700K, 3000K, 3500K, 4000K, 5000K or 5700K CCT, -40°C to 40°C operating range, optional 50°C high ambient, 120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation, IP66 rated housing and light square, 3G vibration rated, Pole, mast-arm or wall-mounted configurations, Five-year warranty

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 2200 K |
| Nominal lamp power | 162 W    | CRI         | 70     |
| Total flux         | 16270 lm | LOR         | 100%   |
| Luminous efficacy  | 100 lm/W | Total power | 162 W  |

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 30.00 in

Width: 12.00 in

Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 162 W

## Protection

IP: 47