Product data sheet


HELEDON MAXI A
931228.003.2.76
RZB



IP 20 IK 06

Series: HELEDON maxi Cylindrical surface-mounted downlight. Housing made of die-cast aluminium, powder-coated. Internal ceiling frame polycarbonate with bayonet mounting. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Suitable for Ceiling mounting. Easy installation with a separate ceiling frame with bayonet mounting and plug connection. Driver integrated. Connected via plug-in connector. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: deep black, matt (RAL 9005) Diameter: 123 mm Height: 183 mm Lamp: LED Socket: without socket Colour temperature: 2700K Colour rendering index (CRI): 90 System power: 36 W Rated luminous flux: 3450 lm Beam angle Down: 31° Luminous efficiency: 96 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	36 W	CRI	90
Total flux	3450 lm	LOR	67%
Luminous efficacy	96 lm/W	ULOR	14%
		Total power	36 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.20 in
Diameter: 4.84 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 36 W

Protection

IP: 20
IK: 06