

Product data sheet

FLAT POLYMERO
311594.002.2
RZB




IP
40

IK
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 150 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1750lm System power: 18W Beam Angle: 117° Number of fittings B10A: 17 Number of fittings B16A: 28 Inrush current: 53A Unified Glare Ratio: 17,9 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	1750 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	9%
		Total power	18 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.91 in
Diameter: 20.28 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 40
IK: 10