



# Product data sheet

STYLUS RECESSED 600MM  
00-5982-05-05  
LEDSC4



LedsC4 Stylus Recessed 600mm 00-5982-05-05V3 Pendant for indoor use. For downlighting. Structure material: Aluminium. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Transparent. Warranty: 2 Years. Product net weight (Kg): 0.83 Product width or diameter (mm): 97 Product height (mm): 2230 Ø of the hole for recessing (mm): 65 Permitted ceiling thickness: 3-30 Class 2. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: HEP. Maximum power of light source: 7.7W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 24.7. Photobiological risk: RG1. Real flux (lm): 412. Real lm/W: 42. Voltage / frequency range: 100-240/50-60Hz. Voltage: 15. Equipment included: Yes. Total power: 9.7. Power factor: 0.90. Dimmable equipment included: ON-OFF.

## Light output 1



1 x LED			
Nominal lamp power	9.7 W	LOR	100%
Lamp flux	412 lm	Total flux	412 lm
Luminous efficacy	42 lm/W	Total power	9.7 W
CCT	3000 K		
CRI	90		

## Mounting mode

Pendant, Table luminaire

## Shape and measurements

Length: 1.18 in

Width: 1.18 in

Height: 23.62 in

## Adjustability

Fixed

## Electric

System power: 9.7 W

Appliance Class: II

## Protection

IP: 20