Product data sheet

745 4000K CRI 80 19W CLD-E WHITE
112600-1957
DISANO



Housing: vandal-resistant, self-extinguishing polycarbonate. Diffuser: In clear polycarbonate, anti-dazzle, vandal resistant. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: supplied with bracket for ceiling/wall installation. Sensors: SENSOR - TECHNICAL SPECIFICATIONS Detection area: 75% Detection distance: ø 4-6 m (adjustable) Hold time: 1 min Ambient light: Disable Power consumption: ~ 0,9 W Microwave frequency/power: 5.8GHz / <lt/>0.3mW Operating temperature: -25°C ÷ 60°C

Light output 1



1 x LED

Nominal lamp power	19 W	LOR	100%
Lamp flux	2026 lm	Total flux	2026 lm
Luminous efficacy	107 lm/W	Total power	19 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.48 in
Diameter: 11.02 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W
Appliance Class: II

Protection

IP: 65
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 41...95°F