
Product data sheet

CALEO SUSPENDED - G1
AG1OSE-830M-L900-Y
LIGHTNET



LED pendant luminaire. Direct only or direct-indirect light distribution. Luminaire body made of aluminum profile. Surface silver, white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable Y-cord suspension with transparent power supply cable. On request: Integration of emergency lighting components, soft-touch black or red sheathed supply line.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	21 W	CRI	82
Total flux	2160 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	21 W

Mounting mode

Pendant

Shape and measurements

Length: 35.43 in
Width: 7.87 in
Height: 2.17 in

Adjustability

Height adjustable

Electric

System power: 21 W

Protection