Product data sheet


LITELINE LP66+ 1500 55W 1050MA 840
7219269
HIDE-A-LITE



IP 66 IK 07

Liteline IP66+ is a luminaire for demanding environments, designed to withstand corrosive conditions and suitable for spaces such as pig pens, cow sheds, and horse stables. The well-thought-out design allows connection and access to the driver without opening the diffuser. Control the lighting via On/Off or DALI. The sliding brackets make installation quick and smooth. With Liteline IP66+, you get replaceable LED and driver, and the option to choose colour temperature 3000K/4000K and adjust the light output via DIP-switch. Through-wiring On/Off 5x2.5 mm². M20 cable gland on each end cap and an extra accessory with 2x M20 cable glands if needed. Suitable for mounting on trunking rail, keyholes for ceiling mounting, and integrated wire suspension with hook and hook lock. D-marked for protection against increased fire risk.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	55.3 W	CRI	80
Total flux	8551 lm	LOR	100%
Luminous efficacy	155 lm/W	ULOR	2%
		Total power	55.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 62.80 in
Width: 3.03 in
Height: 2.83 in

Adjustability

Fixed

Design

Designer: Elektro Elco AB

Electric

System power: 55.3 W
Appliance Class: I

Protection

IP: 66
IK: 07
Designation labels: CE