



# Product data sheet

6500K CRI 80 34W CLD GREY  
22178371-0083  
DISANO



Housing: in polycarbonate, shatterproof and V2 self-extinguishing, UV stabilised, anti-yellowing. Diffuser: in polycarbonate, shatterproof and self-extinguishing, UV stabilised. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: -steel brackets for ceiling and suspension mounting. -socket-plug connector. -The equipment is secured to the mounting brackets by means of a quick-release coupling. Warnings: ATTENTION ! Do not install on surfaces subject to strong vibrations, outdoors on hanging cables, or on walls under metallic grates, or on poles, and in any case, never expose the fixture to direct sunlight. Check the compatibility between the material constituting the product and the space where it will be installed. We recommend the use of fixtures made of steel with direct exposure to sunlight.

## Light output 1



1 x LED			
Nominal lamp power	34 W	LOR	100%
Lamp flux	4800 lm	ULOR	6%
Luminous efficacy	141 lm/W	Total flux	4800 lm
CCT	6500 K	Total power	34 W
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 47.24 in

Width: 2.99 in

Height: 2.60 in

## Adjustability

Fixed

## Electric

System power: 34 W

Appliance Class: I

## Protection

IP: 65

IK: 08

Designation labels: CE