


# Product data sheet


ALEA SPOT  
641318.003.1.76  
RZB



IP  
20

Series: Alea Spot Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Pole: aluminium. Cover: plastic sphere, opal, satin finish. "Triple lamp; mains connection through pole to terminal in" "pole top; base plate: D 300. 4 mounting holes: D 10; pitch" circle for holes: D 230. Available Colours: black Type of Installation: Recessed ceiling mounting Dimensions: L 586, B 75, H 2 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 1950lm System power: 15W Beam Angle: 60°/58° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 16,8 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15 W	CRI	80
Total flux	1950 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	15 W

## Mounting mode

Wall recessed

## Shape and measurements

Length: 2.95 in  
Width: 23.07 in  
Height: 1.46 in

## Adjustability

Fixed

## Electric

System power: 15 W

## Protection

IP: 20