Product data sheet

161PX PROXIMA LED DAMP-PROOF LIGHT FITTING
161PX 15L34 T40 H70 (16134 0023)
SCHUCH



IP 65 IK 08

LED damp-proof light fitting, PROXIMA, 21 W, 3430 lm, 163 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -40 °C/+70 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PC satined, Closure Plastic, Housing Glass fibre reinforced polyester, Colour grey. Sturdy LED damp-proof light fitting for high ambient temperatures and wide temperature ranges. Highly impact-resistant glass fibre reinforced polyester housing and frosted diffuser with high mechanical resistance. Captive safety clips, multi-part, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. FastFix mounting system with sliding stainless steel mounting clips and brackets for chain suspension. Length 1578,00 mm, Width/Diameter 137,00 mm, Height 115,00 mm, Net weight 3,40 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	3430 lm	LOR	100%
Luminous efficacy	163 lm/W	ULOR	7%
		Total power	21 W

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 62.13 in
Width: 5.39 in
Height: 4.53 in

Adjustability

Fixed

Electric

System power: 21 W
Appliance Class: I

Protection

IP: 65
IK: 08
Designation labels: CE