Product data sheet

CODEMASTER LED 250 W NEMA TYPE V WIDE 4000 K CCT CLEAR GLASS, TYPE V WIDE CMLEDA25NGWBU


APPLETON (EMERSON EGS)





Codemaster LED Factory Sealed Luminaire Explosionproof, Dust-Ignitionproof 100W equivalent LED Pendant Mount 120-277V, 50/60Hz 3/4" NPT Hub Clear Glass Globe TYPE V wide Class I, Division 1 & 2, Groups B, C, D Class I, Zone 1, Group IIB + H2 Class II, Division 1, Group E,F, G Class II, Division 2, group F,G. Class III Simultaneous Exposure Type 3R, 4X IP66/67 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) Refer to catalog for additional options

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	76.5 W	CRI	80
Total flux	8789 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	76.5 W

Mounting mode

Pendant

Shape and measurements

Height: 10.08 in Diameter: 7.50 in

Adjustability

Fixed

Electric

System power: 76.5 W Appliance Class: I

Protection

IP: 67 IK: 08 Explosion zone suitability: 1