Product data sheet


MAXOS FUSION LL512X XA 1 XLED50S/830 DA45 LL500X

PHILIPS



Guaranteed performance, thinking ahead Maxos fusion is an adaptable LED trunking system that offers an excellent quality of light while more than halving energy costs compared to fluorescent lamps. For retail applications, a family of linear panels, non-linear modules and a spot portfolio can be smoothly integrated into the track backbone to let your merchandise sparkle and stand out. For industrial applications, the focus is on reducing installation and maintenance cost by using fewer linear panels. With the electrical set-up of up to 13 wires, the freedom to position these fixtures as required and the integration of other services/third-party hardware, the system allows you to reduce ceiling clutter. It can also be easily re-configured to accommodate future lay-out changes. The infrastructure is enabled to integrate sensors for data collection, giving you the opportunity to use insightful granular information to support your business.

Light output 1



1 x LED

Nominal lamp power	28.8 W	LOR	100%
Lamp flux	4800 lm	Total flux	4802 lm
Luminous efficacy	167 lm/W	Total power	28.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.80 in
Width: 2.44 in
Height: 2.20 in

Electric

System power: 28.8 W