


# Product data sheet

HOME 105  
611984.0031  
RZB




IP  
54

IK  
06

Series: Home 105 Type of Protection: IP 54 Protection Class: I Voltage: 200 - 240 V / 50 - 60 Hz Wall luminaire, direct beam. Housing: pressure die-cast aluminium, powder-coated. Driver included. LED included. Available Colours: anthracite metallic Type of Installation: Wall (surface) Dimensions: L 80, B 66, H 75 Lamp: LED Life time: 25000 h (L70/B50) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 110lm System power: 4W Beam Angle: 35°/19°/43°/43° Number of fittings B10A: 200 Number of fittings B16A: 320 Inrush current: 40A Unified Glare Ratio: 22,2 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	80
Total flux	110 lm	LOR	100%
Luminous efficacy	28 lm/W	ULOR	2%
		Total power	4 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 2.60 in  
Width: 3.15 in  
Height: 2.95 in

## Adjustability

Fixed

## Electric

System power: 4 W

## Protection

IP: 54  
IK: 06