Product data sheet

MIC 5 FLOODLIGHTS,PROJECTORS MI-50393-W-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	52.1 W	CRI	80
Total flux	5989 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	52.1 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 14.76 in Diameter: 10.28 in Weight: 5.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 52.1 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65 IK: 07

Surface temperature: 40°C