


# Product data sheet

MATRIC 55MM WALL DIRECT - D3  
LD3AEE-840M-L1765  
LIGHTNET



LED wall mounted luminaire. Direct only light distribution. Light channel made of aluminium profile with 55mm track width. Precise length production according to specifications possible. Surface natural anodised or white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen and satin louver for office purposes. Opal diffuser made of acrylic glass for general lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial  $\leq$  MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components, sensor technology.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40 W	CRI	82
Total flux	3170 lm	LOR	100%
Luminous efficacy	79 lm/W	Total power	40 W

## Mounting mode

Wall mounted

## Electric

System power: 40 W

## Shape and measurements

Length: 69.49 in  
Width: 2.17 in  
Height: 2.95 in

## Protection

## Adjustability

Fixed