


# Product data sheet

PRO-BEAM 170W 60°  
4106155X  
PROLUMIA




Light source: 160W Beam angle: 15° / 30° / 40° / 60° / 60°x135° / 85°x135° Color temperature: 3000K (Warm white), 4000K (Pure white), 6000K (Cool white) Light output: 16.175LM/17.975LM/19.550LM Color rendering index: Ra ≥ 70\* Operating temperature: -40°C - +45°C Rated life hours: 50.000 LED driver (included): CE Input: 90-305V AC 50/60Hz Power factor: > 0.95 Power consumption (driver included): Max 170W

## Light output 1




### 1 x LED

Nominal lamp power	170 W	LOR	100%
Lamp flux	19550 lm	Total flux	19550 lm
Luminous efficacy	115 lm/W	Total power	170 W
CCT	6500 K		
CRI	80		



### 1 x LED

Nominal lamp power	170 W	LOR	100%
Lamp flux	17975 lm	Total flux	17975 lm
Luminous efficacy	106 lm/W	Total power	170 W
CCT	4000 K		
CRI	80		



### 1 x LED

Nominal lamp power	170 W	LOR	100%
Lamp flux	16175 lm	Total flux	16175 lm
Luminous efficacy	95 lm/W	Total power	170 W
CCT	3000 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Electric

System power: 170 W  
Appliance Class: 0

### Shape and measurements

Length: 15.24 in

Width: 14.45 in

Height: 3.58 in

### Protection

IP: 65

IK: 10

Designation labels: CE, GS