

Product data sheet

O69-R125 LED 800 HF 840 WB
GLAMOX




IP
65

IK
05

Light source LED 2000 - 3600 lumen out Colour temperature 3000/4000 K, CRI Ra 85, MacAdams 3 Driver Supplied with external IP20 driver. Fixed output (HF) or DALI dimmable (100-1%). Body material & colour Housing in die-cast aluminium with white polyester powder coated paint finish (close to RAL 9010). The front cover is made of tempered glass. Silicone gasket. Screws are in stainless steel. Mounting For recessed installation into a ceiling with thickness of 1 - 20 mm. The luminaire must not be covered with thermally insulating material. Connection 3 pole (HF) or 5 pole (DALI) 2.5 mm² push-in terminal block prepared for through wiring on external driver. Optics Medium beam (MB) and wide beam (WB). Housing Equipped with a pressure equalisation filter to prevent the formation of condensation.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	818 lm	LOR	100%
Luminous efficacy	82 lm/W	ULOR	84%
		Total power	10 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.56 in
Diameter: 4.92 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W

Protection

IP: 65
IK: 05