


Product data sheet

HIDE FLOOR WITH REFLECTOR300MM (BLACK)
7383106
ZERO



Finish: White or black-painted steel. With hidden light source behind opalacrylic diffuser, model with reflector is open. Other colors on request.
Connection: 2,5m cable with switch and plug. Design: Thomas Bernstrand


Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W
Lamp flux	3200 lm
Luminous efficacy	26 lm/W
CCT	3000 K
CRI	85


Socket	Gx24Q-4
LOR	34%
Total flux	1089 lm
Total power	42 W



1 x Compact fluorescent lamp

Nominal lamp power	32 W
Lamp flux	2400 lm
Luminous efficacy	19 lm/W
CCT	3000 K
CRI	85

Socket	Gx24Q-3
LOR	34%
Total flux	817 lm
Total power	42 W



1 x Compact fluorescent lamp

Nominal lamp power	26 W
Lamp flux	1800 lm
Luminous efficacy	15 lm/W
CCT	3000 K
CRI	85

Socket	Gx24Q-3
LOR	34%
Total flux	613 lm
Total power	42 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 21.16 in

Width: 11.91 in

Height: 72.83 in

Adjustability

Fixed

Electric

System power: 42 W

Controller: DALI

Suitable for feed-through wiring

Appliance Class: I

Protection

IP: 20

Designation labels: CE