
Product data sheet

LUCAS IX (1-ARMED) 9.859.3062.15

LEIPZIGER LEUCHTEN








Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury | vapour lamp | |
|---------------------------|-------------|---------|
| Nominal lamp power | 125 W | LOR |
| Lamp flux | 6800 lm | ULOR |
| Luminous efficacy | 40 lm/W | Total f |
| CCT | 3400 K | Total p |
| CRI | 54 | |

| OLON | 47 |
|-------------|---------|
| Total flux | 5416 ln |
| Total power | 137 V |
| | |

80%

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 137 W

Protection

IP: 55