



Product data sheet

CIRCULAR INWARD 5 RINGS (Ø1200 Ø2000 Ø3000 Ø2000 Ø1200)
CD4E-00W9AZDU14
LEDSC4




LedsC4 Circular Inward 5 Rings (Ø1200 Ø2000 Ø3000 Ø2000 Ø1200) CD4E-00W9AZDU14V1 Pendant for indoor use. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 3030 Product height (mm): 6500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 562W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 32310. Real lm/W: 56. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 575. Power factor: 0.90. Dimmable equipment included: DALI.

Light output 1




1 x LED			
Nominal lamp power	68.8 W	LOR	100%
Lamp flux	4030 lm	ULOR	50%
Luminous efficacy	59 lm/W	Total flux	4030 lm
CCT	3000 K	Total power	68.8 W
CRI	90		

Light output 2




1 x LED			
Nominal lamp power	68.8 W	LOR	100%
Lamp flux	4030 lm	ULOR	50%
Luminous efficacy	59 lm/W	Total flux	4030 lm
CCT	3000 K	Total power	68.8 W
CRI	90		

Light output 3




1 x LED			
Nominal lamp power	125.8 W	LOR	100%
Lamp flux	7021 lm	ULOR	50%
Luminous efficacy	56 lm/W	Total flux	7021 lm
CCT	3000 K	Total power	125.8 W
CRI	90		

Light output 4



1 x LED			
Nominal lamp power	184.7 W	LOR	100%
Lamp flux	10208 lm	ULOR	50%
Luminous efficacy	55 lm/W	Total flux	10208 lm
CCT	3000 K	Total power	184.7 W
CRI	90		

Light output 5



1 x LED			
Nominal lamp power	125.8 W	LOR	100%
Lamp flux	7021 lm	ULOR	50%
Luminous efficacy	56 lm/W	Total flux	7021 lm
CCT	3000 K	Total power	125.8 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 47.24 in

Width: 47.24 in

Height: 1.18 in

Adjustability

Fixed

Electric

System power: 573.9 W

Appliance Class: I

Protection

IP: 20