


Product data sheet

VERDA ASYM WITH SHADE CL II 830 CLO CG
305077-565
FAGERHULT



Installation Luminaire for assembly on a post, with post top Ø 60 mm. Connection Supplied with 5 m 2x1,5 mm² connection cable (H07RN-F). Design Body, heat sink and cover in cast aluminium. Diffuser of impact resistant UV-stabilised polycarbonate. Shade of enamelled aluminium, wet enamelled underside. Ballast integrated in the luminaire. Reflector Symmetrical reflector in acrylic (PMMA) or asymmetrical reflector in sheet metal. Light distribution Symmetrical or asymmetrical. Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life. Other options for light control available on request. For more information, see Light control. Standard Colour Anthracite grey (Gris 900 Sablé). Miscellaneous Projected area: from the side 0.105 m², from above 0.058 m². Luminaire weight: 6.3 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	3184 lm	LOR	100%
Luminous efficacy	88 lm/W	ULOR	7%
		Total power	36 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 22.64 in

Width: 22.81 in

Height: 21.20 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 66