

Product data sheet

WALLWASHER 6 RGBW


L1307B

PROLED (MBN GMBH)




The PROLED WALLWASHER 6 RGBW is ideal for the illumination of large surfaces, e.g. buildings or walls in outdoor areas. They are also suitable for ambient lighting in indoor applications. Because of the RGBW high power LEDs (4 Watt) the RGBW WALLWASHER 6 offers homogeneous colormixing and clean natural white. - dimmable, autom. colour change, controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies or PRO CONTROLLER

Light output 1 (integrated)




Lamp type	LED	CCT	7247 K
Nominal lamp power	8.7 W	CRI	-18
Total flux	500 lm	LOR	100%
Luminous efficacy	57 lm/W	Total power	8.7 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	7 W	CRI	-29
Total flux	250 lm	LOR	100%
Luminous efficacy	36 lm/W	Total power	7 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	8.7 W	CRI	-50
Total flux	120 lm	LOR	100%
Luminous efficacy	14 lm/W	Total power	8.7 W

Light output 4 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	8.7 W	CRI	70
Total flux	700 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	8.7 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 6.50 in
Width: 2.40 in
Height: 9.33 in
Weight: 2.3 kg

Adjustability

Tiltable

Electric

System power: 33.1 W
Controller: Dimmable 1..10V, DMX, DALI
Color adjustable
Appliance Class: III

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: 14...113°F