Product data sheet

MOTUS PENDANT 180 700 827 GLAMOX








Light source LED 500-700 lumen out Colour temperature 2700, 3000 or 4000 K, CRI Ra 80 (90 on request), MacAdams 3 Tuneable white 2700-6500 K Driver DALI driver combined with switch/dim for dimming with regular push button Driver mounted in ceiling cup AC driver integrated in LED module for ON/OFF control or with phase-cut dimming. Body material & colour Powder painted steel shade in matt black or white. Also available in Luxo Colour Concept, see colour codes underneath Estate Green - S 4520-G Pleasant Green - S 2520-G30Y Silk Teal - S 2015-B70G Mild Citrus - S 1015-G50Y Connection DALI - 5 pole 2x2,5 mm² push-in terminal block for mains connection in ceiling cup AC - 3 pole 2x2,5 mm² push-in terminal block for mains connection in ceiling cup Optics An oval opal diffusor inside of the steel shade Mounting 2 or 5 meter halogen/PVC free textile cable in white or black

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	7 W	CRI	80
Total flux	617 lm	LOR	100%
Luminous efficacy	88 lm/W	ULOR	84%
		Total power	7 W

Mounting mode

Pendant

Shape and measurements

Height: 3.94 in Diameter: 7.09 in

Adjustability

Height adjustable

Electric

System power: 7 W

Protection

IP: 20