



# Product data sheet

NOTUS 1 CROSS LOW UGR 4274MM  
830  
BRIGHT SPECIAL LIGHTING




Housing :Extruded aluminium Diffuser :Extruded PMMA | Cross Control Gear :Built-in electronic driver UGR :≤19 with special covers  
Transmittance :80% IP :40 IK :04

## Light output 1



|                    |          |             |          |
|--------------------|----------|-------------|----------|
| 1 x LED            |          |             |          |
| Nominal lamp power | 116.7 W  | LOR         | 100%     |
| Lamp flux          | 17088 lm | Total flux  | 17088 lm |
| Luminous efficacy  | 146 lm/W | Total power | 116.7 W  |
| CCT                | 3114 K   |             |          |
| CRI                | 83       |             |          |



|                    |          |             |          |
|--------------------|----------|-------------|----------|
| 1 x LED            |          |             |          |
| Nominal lamp power | 84.9 W   | LOR         | 100%     |
| Lamp flux          | 11552 lm | Total flux  | 11552 lm |
| Luminous efficacy  | 136 lm/W | Total power | 84.9 W   |
| CCT                | 3114 K   |             |          |
| CRI                | 83       |             |          |

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 168.27 in  
Width: 3.15 in  
Height: 3.50 in

## Adjustability

Free

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 84.9-116.7 W  
Ballast: ECG  
Controller: Dimmable 0..10V, Dimmable 1..10V, DALI  
Color adjustable  
Appliance Class: I

## Protection

IP: 40  
IK: 04