


Product data sheet

RECESSO BETA OPTI 1CELL 150 830
25712
FAGERHULT



Installation Recessed mounting in suspended ceilings. Only for suspended ceilings with visible T-bars (15 or 25 mm). Connection Connection to snap-in terminal block 3-way or 5-way, 2,5 mm². Can also be supplied with mains cable and earthed plug. Can also be equipped with the Wieland or Wago connection system. Design Body of white enamelled (RAL 9016) sheet steel. Openings along the entire body, outside the edge of the louvre for flow-through ventilation. Louvre Beta Opti – double parabolic side and cross reflectors in satin matt, metallized aluminium with ex-cellent reflective properties (>92 %), integrated into a single unit. Integrated in the unit, an acrylic (PMMA) diffuser film to create optimised light technology properties. The louvre in its standard design is equipped with protective foil over the light opening. The protective foil is easily removed after final cleaning/installation.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	3944 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	30 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.13 in
Width: 5.79 in
Height: 3.46 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 30 W

Protection

IP: 20