Product data sheet

OUTDOOR LIGHTING

V1-S1-70442-40W30-6624040 TORNADO AWADA 240W 4000K PLC


VARTON



IP 66 IK 09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: roads and streets with AWADA control system. Installation: pole and side-entry mounted (Ø48mm-60mm). Power factor: 0,97 AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-asuno-awada-plc/svetodiodnyy-svetilnik-varton-ulichnyy-tornado-urban-240-vt-kreplenie-na-konsol-4000-k-ral7045-seryy/

Light output 1



1 x LED

Nominal lamp power	240 W	LOR	100%
Lamp flux	32400 lm	Total flux	32400 lm
Luminous efficacy	135 lm/W	Total power	240 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 33.07 in
Width: 12.20 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 240 W

Protection

IP: 66
IK: 09