


Product data sheet

TOLDBOD 220 WALL 100W E27
5743160529
LOUIS POULSEN



Tolddbod 220/290 Wall Design : Louis Poulsen Lighting A/S Concept : The light is directed 100% downwards and the shade has a matte white painted interior emitting a soft, diffused, comfortable light. Finish : Aluminium coloured with textured surface or black with textured surface, powder coated. Material : Fixture head: Die cast aluminium. Shield: Injection moulded clear polycarbonate. Wall box: Die cast aluminium. Arm: Extruded aluminium. Mounting : Terminal block: 1x3x2.5mm². Cable entries: Ø 290: 2x rear entries and 2x bottom entries to Ø 10- 14.5mm cable. Ø 220: 3x rear entries and 2x knock outs in bottom to Ø 10-14.5mm cable. Looping: Approved, max. 3x1,5mm². Class : Ingress protection, Ø 220: IP43, Ø 290: IP44. Electric shock protection I w. ground, II w/o ground. Weight : Max. 5kg.

Light output 1



1 x General service incandescent lamp

Nominal lamp power	100 W	LOR	72%
Lamp flux	1380 lm	Total flux	995 lm
Luminous efficacy	10 lm/W	Total power	100 W
CCT			
CRI			

Mounting mode

Wall mounted

Shape and measurements

Height: 8.66 in
Diameter: 8.86 in

Adjustability

Fixed

Electric

System power: 100 W
Appliance Class: I

Protection

IP: 44