Product data sheet


INFINITE PRO 1136MM SURFACE ELIPTIC
AK14-34X8E2OSN3
LEDSC4



IP 40

LedsC4 Infinite Pro 1136mm Surface Eliptic AK14-34X8E2OSN3V2 Lineal lighting system for indoor use. For downlighting. Structure finish: Grey. Diffuser material: Polycarbonate. Diffuser finish: Eliptic. Warranty: 5 Years. Product net weight (Kg): 2.86 Product length (mm): 1136 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP40. LED. No. of lampholders or LEDs: 1. Driver brand: TRIDONIC. Maximum power of light source: 31.1W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 80.000h L80B20. UGR: 18.1. Photobiological risk: RG1. % de Flickering: +/- 5%. Real flux (lm): 5536. Real lm/W: 170. Voltage / frequency range: 220-240/50-60Hz. Voltage: 96. Equipment included: Yes. Total power: 32.6. Power factor: 0.95. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	32.6 W	LOR	100%
Lamp flux	5536 lm	Total flux	5536 lm
Luminous efficacy	170 lm/W	Total power	32.6 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 44.72 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 32.6 W
Appliance Class: I

Protection

IP: 40