Product data sheet

THOR B W 10L25 740 R/S CL1 MPL
96264257
THORN LIGHTING



IP 66 IK 10

An elegant vandal resistant radially symmetric slim bollard with high performance optic. For Electronic, fixed output control gear. IP66 Electrical Class I. Column and Base: aluminium (EW AW 6060). Canopy: die-cast aluminium (EN AC 47100). Diffuser: Clear anti UV polycarbonate. Gear Box: polycarbonate. Canopy and Column colour: powder coated dark grey (close to RAL7043). Ready to install prewired luminaire. Connection box required, to be ordered separately. Complete with 4000K LED Flange mounting: 4 x anchor bolts M14 (to be ordered separately), spacing: 200mm Dimensions: 250 x 250 x 541 mm Total power: 11 W Weight: 9 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11 W	CRI	70
Total flux	741 lm	LOR	100%
Luminous efficacy	67 lm/W	ULOR	5%
		Total power	11 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 21.30 in
Diameter: 9.84 in
Weight: 9 kg

Design

Material impression: Aluminum

Electric

System power: 11 W
Voltage: 230 V AC
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE