




Product data sheet

SINTESI SYSTEM - CEILING - DARK OPTICS - UGR<lt/>19 3000K CRI 80 29W CLD WHITE
22010010-39
DISANO



Housing: in extruded 6060 aluminium alloy. Removable extruded aluminium 6060 alloy top cover to allow electrical line connection. Injection-moulded ABS V0 end caps. Optics: dark light double parabolic louvers in high gloss 99.99 aluminium, anti-dazzle and anti-iridescent, very low luminance, and PDV treatment. : UGR<lt/>19, according to standard EN 12464. Coating: epoxy polyester powder coating resistant to UV rays. LED: 80%: 50000h (L80B20) Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529.

Light output 1



1 x LED			
Nominal lamp power	29 W	LOR	100%
Lamp flux	2335 lm	Total flux	2335 lm
Luminous efficacy	81 lm/W	Total power	29 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 45.91 in

Width: 2.76 in

Height: 3.50 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: White

Electric

System power: 29 W

Appliance Class: I

Protection

IP: 40

IK: 07

Designation labels: CE