


# Product data sheet

ATLANTYK 2.0 BASIC LED 1245 DALI 40W 5900LM 4000K POLYCARBONATE IP65 GRAPHITE  
090380.3L04.021  
LUG



Hermetic LED luminaire, water-jet proof, intended for mounting inside industrial or architectural objects. Luminaire with Easy Connect.  
Mounting: directly on the ceiling, with mounting brackets (included), suspended, on chains, on wire suspension (on request) Body: plastic  
Power: 220-240V 50/60Hz Lifetime (L80B10): 100 000 h Available on request: available with connection to a central battery power supply, radar motion detector, twilight sensor Warranty: 5 years Application: parking areas, production halls, warehouses, assembly halls, warehouses, electricity plants, mills, workshops, wood and paper industry Type of optics: opal diffuser

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40 W	CRI	80
Total flux	5900 lm	LOR	100%
Luminous efficacy	148 lm/W	ULOR	9%
		Total power	40 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 49.02 in

Width: 3.94 in

Height: 3.54 in

## Adjustability

Fixed

## Design

Color of housing: Anthracite / graphite

## Electric

System power: 40 W

Controller: DALI

Appliance Class: I

## Protection

IP: 65

IK: 08